

Technical Data Sheet

DRVOFRONT

Protective coating for logs



product description:	Acrylic water-based paint for the protection of logs, sawn timber and similar wooden forms. It is a medium-viscous, homogeneous mass that creates an elastic film with good adhesion and weather resistance on wood.
area of application:	The protective coating for wood is used with the intention of preventing or reducing the cracking of wood during rapid drying and reducing the congestion and cracking of wood. It is used on stored logs, sawn timber and similar wooden sawn forms or for drying in dryers.
assortment:	DRVOFRONT protective coating for logs is produced in blue colour and according to the customer's request.
thinner:	It does not dilute.
coverage:	3 – 5 m ² /kg
density:	1.6 – 1.7 kg/l (EN ISO 2811-1)
viscosity:	2400 -3200 mPa·s (EN ISO 2555)
pH:	6 – 8
non-volatile-matter content:	70±2 % (EN ISO 3251, Φ 75 mm, 105°C, 1h)
volatile organic compound (VOC) content:	A(d), 130 g/l; max. 40 g/l (EN ISO 11890-1)
working conditions:	The temperature of the air, material and substrate during processing must be higher than +10 ° C, less than +25 ° C, and relative humidity less than 75 %.
application:	DRVOFRONT is intended for spraying. The coating is factory prepared for use, and must be mixed well before use. It can be applied by brush or immersion, but care should be taken with the thickness of the film. After finishing the work, it is recommended to wash the tool with water, and to seal the remaining amount well. For any additional info, please contact a Chromos-Svjetlost technical advisor.
safety measures:	DRVOFRONT is non-flammable, not toxic or harmful to health. In case of accident, immediately rinse DRVOFRONT with cold water. It meets the strictest criteria for the protection of human health and the environment.
transport and storage:	Store in a dry and well-ventilated place out of direct sunlight at a temperature of +5 to +25 °C. Protect it from freezing.
shelf life:	In unopened packaging 18 months from the date of production.
note:	Protect from freezing!
certificates:	For each production batch, the relevant documentation is submitted.
product/packaging disposal:	Empty the packaging completely. Dispose of in accordance with valid regulations to an authorized waste collector.
quality control:	Product quality characteristics are determined by internal production specifications, as well as European and Croatian standards. The product is under the constant supervision of factory quality control Chromos-Svjetlost d.o.o.
disclaimers:	Before using the product, please check its quality. In case of any major deviations from the declared properties of the product, stop the use and contact the manufacturer;

Technical Data Sheet

DRVOFRONT

Protective coating for logs



otherwise any subsequent complaints will not be accepted.

Technical data are the result of our technical and experimental knowledge, and are provided with the intention of achieving optimal results in working with CHROMOS-SVJETLOST products. The data does not contain a legal or secondary obligation of the manufacturer nor does it release the user from the obligation to check the suitability of the product for particular purpose. Due to the use of natural raw materials in our products, minor deviations from certain values are possible for individual deliveries. Contact our Technical service before use on substrates not listed in the accompanying documentation. The manufacturer reserves the right to make any subsequent changes to the Technical Data Sheet. Only the latest edition is valid. Updated Technical Data Sheets can be found on the website www.chromos-svjetlost.hr or can be requested from the manufacturer via the contact e-mail address below. Contact our Technical service for more detailed information. Be sure to read the safety labels on the product packaging before use. Safety Data Sheet is available on request.

October, 2021.

Quality and Environmental management systems certified in accordance with TÜV NORD Croatia;
Certificate No: 44 100 134668 / 44 104 134668

